



- ① Series name
- ② Dual output
- ③ Output wattage
- ④ Input voltage
- ⑤ Output voltage

| MODEL | ZUW100512 | ZUW100515 | ZUW101212 | ZUW101215 | ZUW102412 | ZUW102415 | ZUW104812 | ZUW104815 | |
|-----------------------|------------|------------|------------|------------|------------|------------|------------|------------|------------|
| MAX OUTPUT WATTAGE[W] | 8.4 | 9.0 | 10.8 | 10.5 | 10.8 | 10.5 | 10.8 | 10.5 | |
| DC OUTPUT | VOLTAGE[V] | ±12 or +24 | ±15 or +30 | ±12 or +24 | ±15 or +30 | ±12 or +24 | ±15 or +30 | ±12 or +24 | ±15 or +30 |
| | CURRENT[A] | 0.35 | 0.30 | 0.45 | 0.35 | 0.45 | 0.35 | 0.45 | 0.35 |

SPECIFICATIONS

Output pins can be connected in series to make a 24V/30V output.

| | MODEL | ZUW100512 | ZUW100515 | ZUW101212 | ZUW101215 | ZUW102412 | ZUW102415 | ZUW104812 | ZUW104815 | |
|---------------------------|--------------------------------------|--|---------------|---------------|---------------|---------------|---------------|---------------|-----------|--------|
| INPUT | VOLTAGE[V] | DC4.5 - 9 | | DC9 - 18 | | DC18 - 36 | | DC36 - 72 | | |
| | CURRENT[A] | *1 2.24typ | 2.40typ | 1.12typ | 1.09typ | 0.56typ | 0.55typ | 0.28typ | 0.28typ | |
| | EFFICIENCY[%] | *1 75typ | 75typ | 81typ | 81typ | 81typ | 81typ | 81typ | 81typ | |
| OUTPUT | VOLTAGE[V] | ±12 (+24) | ±15 (+30) | ±12 (+24) | ±15 (+30) | ±12 (+24) | ±15 (+30) | ±12 (+24) | ±15 (+30) | |
| | CURRENT[A] | 0.35 | 0.30 | 0.45 | 0.35 | 0.45 | 0.35 | 0.45 | 0.35 | |
| | LINE REGULATION[mV] | 60max | 75max | 60max | 75max | 60max | 75max | 60max | 75max | |
| | LOAD REGULATION[mV] | 600max | 750max | 600max | 750max | 600max | 750max | 600max | 750max | |
| | RIPPLE[mVp-p] | *2 120max | 120max | 120max | 120max | 120max | 120max | 120max | 120max | |
| | RIPPLE NOISE[mVp-p] | *2 150max | 150max | 150max | 150max | 150max | 150max | 150max | 150max | |
| | TEMPERATURE REGULATION[mV] | -20 to +55°C | 150max | 180max | 150max | 180max | 150max | 180max | 150max | 180max |
| | DRIFT[mV] | *3 50max | 60max | 50max | 60max | 50max | 60max | 50max | 60max | |
| | START-UP TIME[ms] | 20max (Minimum input, I _o =100%) | | | | | | | | |
| | OUTPUT VOLTAGE ADJUSTMENT RANGE[V] | Fixed | | | | | | | | |
| OUTPUT VOLTAGE SETTING[V] | 11.40 - 12.60 | 14.25 - 15.75 | 11.40 - 12.60 | 14.25 - 15.75 | 11.40 - 12.60 | 14.25 - 15.75 | 11.40 - 12.60 | 14.25 - 15.75 | | |
| PROTECTION CIRCUIT | OVERCURRENT PROTECTION | Works over 105% of rating and recovers automatically | | | | | | | | |
| ISOLATION | INPUT-OUTPUT | AC500V 1minute, Cutoff current = 10mA, DC500V 50MΩ min (20±15°C) | | | | | | | | |
| | INPUT-CASE | AC500V 1minute, Cutoff current = 10mA, DC500V 50MΩ min (20±15°C) | | | | | | | | |
| | OUTPUT-CASE | AC500V 1minute, Cutoff current = 10mA, DC500V 50MΩ min (20±15°C) | | | | | | | | |
| ENVIRONMENT | OPERATING TEMP., HUMID. AND ALTITUDE | -20 to +71°C, 20 - 95%RH (Non condensing) (Refer to DERATING CURVE), 3,000m (10,000feet) max | | | | | | | | |
| | STORAGE TEMP., HUMID. AND ALTITUDE | -40 to +85°C, 20 - 95%RH (Non condensing), 9,000m (30,000feet) max | | | | | | | | |
| | VIBRATION | 10 - 55Hz, 98.0m/s ² (10G), 3minutes period, 60minutes each along X, Y and Z axis | | | | | | | | |
| | IMPACT | 490.3m/s ² (50G), 11ms, once each X, Y and Z axis | | | | | | | | |
| SAFETY | AGENCY APPROVALS | UL1950, EN60950, CSA C22.2 No.950 Complies with IEC60950 | | | | | | | | |
| OTHERS | CASE SIZE/WEIGHT | 45 × 7 × 35mm (W × H × D) / 40g max | | | | | | | | |
| | COOLING METHOD | Convection | | | | | | | | |

*1 Rated input 5V, 12V, 24V or 48V DC, I_o=100%.

*2 Measured by 20MHz oscilloscope.

*3 The drift is a change at 25°C of ambient temperature and 30 minutes - 8 hours after the input voltage applied at rated input/output.

* The output specification is at ±12V and ±15V.

* Series/Parallel operation with other model is not possible.