


## 35W Single Output Series



- High reliability, low cost
- Built-in EMI filter
- 100% full load burn-in test
- Protections: overload/ short circuit
- 1 year warranty
- F603 129 x 98 x 40(mm)

AC input voltage range .....	170~264VAC
Input frequency .....	47~63Hz
Inrush current .....	cold start, 40A/230V
Input leakage current .....	< 0.5mA/ 230VAC
Line regulation (full load) .....	$\leq \pm 0.5\%$
Output voltage adjust range .....	$\pm 10\%$
Output overload protection .....	110~150%
Withstand voltage .....	I/P - O/P: 1.5KVAC/1min
	I/P - F/G: 1.5KVAC/1min
	O/P - F/G: 0.5KVAC/1min
Rise time .....	50ms@full load (typical)
Hold up time .....	20ms@full load (typical)
Operating temp. & humidity .....	-10°C~+50°C, 20%~90%RH (non condensing)
Storage temp. & humidity .....	-20°C~+85°C, 20%~95%RH (non condensing)
MTBF .....	100,000 hours
Safety standards .....	design meet GB4943, UL60950, EN60950
EMC standards .....	meet GB9254, EN55022 classA
	EN61000-3-2,3, EN61000-4-2,3,4,5,6,8,11
Cooling method .....	convection

Model	DC Output		Load regul.	R & N	Efficiency
HF35W-S-5	5V	7.0A	0.5%	60mV	72%
HF35W-S-12	12V	3.0A	0.5%	80mV	74%
HF35W-S-15	15V	2.4A	0.5%	100mV	76%
HF35W-S-24	24V	1.5A	0.5%	100mV	78%
HF35W-S-48	48V	0.8A	0.5%	150mV	79%

## Drawing

