400W Single Output Series

- High reliability, low cost
- Built in fan speed control
- 100% full load burn-in test
- Protections: over current/ over voltage over temperature/ short circuit
- 1 year warranty
- F630 241 x 124 x 65(mm)

AC input voltage range	170~264VAC
Input frequency	47~63Hz
Inrush current	cold start, 40A/230V
Input leakage current	< 0.7mA/ 230VAC
Line regulation (full load)	≤± 0.5%
Output voltage adjust range	± 10%
Output over current protection	105~120%, constant current, auto recovery
Output over voltage protection	115~150%
Withstand voltage	I/P - O/P: 1.5KVAC/1min I/P - F/G: 1.5KVAC/1min O/P- F/G: 0.5KVAC/1min
Rise time	50ms@full load (typical)
Hold up time	20ms@full load (typical)
Operating temp. & humidity	-10℃~+50℃, 20%~90%RH (non condensing)
Storage temp. & humidity	-20℃~+85℃, 20%~95%RH (non condensing)
MTBF	50,000 hours
Safety standards	design refer to GB4943, UL60950, EN60950
EMC standards	design refer to GB9254, EN55022 classA
Cooling method	fan

Model	DC Output		Load regul.	R & N	Efficiency
HF400W-S-9	9V	44A	0.5%	120mV	78%
HF400W-S-12	12V	33A	0.5%	150mV	83%
HF400W-S-24	24V	17A	0.5%	150mV	85%
HF400W-S-36	36V	11A	0.5%	150mV	85%
HF400W-S-48	48V	8.3A	0.5%	200mV	86%

Drawing

F630