

70W Single Output Series



- High reliability, low cost
- Built-in EMI filter
- 100% full load burn-in test
- Protections: overload/ short circuit
- 1 year warranty
- F605 160 x 98 x 39(mm)

AC input voltage range	170~264VAC
Input frequency	47~63Hz
Inrush current	cold start, 40A/230V
Input leakage current	< 0.7mA/ 230VAC
Line regulation (full load)	$\leq \pm 0.5\%$
Output voltage adjust range	$\pm 10\%$
Output overload protection	110~150%
Withstand voltage	I/P - O/P: 1.5KVAC/1min
	I/P - F/G: 1.5KVAC/1min
	O/P - F/G: 0.5KVAC/1min
Rise time	50ms@full load (typical)
Hold up time	20ms@full load (typical)
Operating temp. & humidity	-10°C~+50°C, 20%~90%RH (non condensing)
Storage temp. & humidity	-20°C~+85°C, 20%~95%RH (non condensing)
MTBF	100,000 hours
Safety standards	design meet GB4943, UL60950, EN60950
EMC standards	meet GB9254, EN55022 classA
	EN61000-3-2,3, EN61000-4-2,3,4,5,6,8,11
Cooling method	convection

Model	DC Output		Load regul.	R & N	Efficiency
HF70W-S-12	12V	6.0A	0.5%	100mV	78%
HF70W-S-15	15V	4.7A	0.5%	100mV	79%
HF70W-S-24	24V	3.0A	0.5%	120mV	82%
HF70W-S-27	27V	2.6A	0.5%	120mV	82%
HF70W-S-48	48V	1.5A	0.5%	150mV	83%

Drawing

